



External Dimensions (mm) (HxWxD) Colour RAL 9010 Door Options Solid, Clear e-Fob Positions 3 - 5 Weight 21kg Internal Controller Dimensions (mm) (HxWxD) Colour RAL 7016 Weight 7kg Power Supply (v) 24 Max Power Consumption (A) 1.5 External Communications Ethernet, Wifi Internal Communications CAN bus Operating Temperature -10 +60 System Materials 1.5mm Stainless Steel 304 Warranty 24 Months Service Level Agreement 24 Months Standards CE and FCC		
Door Options e-Fob Positions 3 - 5 Weight 21kg Internal Controller Dimensions (mm) (HxWxD) Colour RAL 7016 Weight 7kg Power Supply (v) Max Power Consumption (A) External Communications Internal Communications CAN bus Operating Temperature System Materials Varranty Service Level Agreement Solid, Clear 3 - 5 200 x 200 x 80 1.50 CAL 7016 CAL 7016 CAL 7016 Tokg CAL 7016 Tokg 1.5 Ethernet, Wifi CAN bus -10 +60 1.5mm Stainless Steel 304 Varranty 24 Months		1618 x 300 x 453
e-Fob Positions Weight Internal Controller Dimensions (mm) (HxWxD) Colour RAL 7016 Weight 7kg Power Supply (v) And Power Consumption (A) External Communications Internal Communications Operating Temperature System Materials Very Canal Communications CAN bus Operating Temperature -10 +60 System Materials 1.5mm Stainless Steel 304 Warranty 24 Months Service Level Agreement 24 Months	Colour	RAL 9010
Weight 21kg Internal Controller Dimensions (mm) (HxWxD) Colour RAL 7016 Weight 7kg Power Supply (v) 24 Max Power Consumption (A) 1.5 External Communications Ethernet, Wifi Internal Communications CAN bus Operating Temperature -10 +60 System Materials 1.5mm Stainless Steel 304 Warranty 24 Months Service Level Agreement 24 Months	Door Options	Solid, Clear
Internal Controller Dimensions (mm) (HxWxD) Colour RAL 7016 Weight 7kg Power Supply (v) 24 Max Power Consumption (A) 1.5 External Communications Ethernet, Wifi Internal Communications CAN bus Operating Temperature -10 +60 System Materials 1.5mm Stainless Steel 304 Warranty 24 Months Service Level Agreement 24 Months	e-Fob Positions	3 - 5
Dimensions (mm) (HxWxD) Colour RAL 7016 Weight 7kg Power Supply (v) 24 Max Power Consumption (A) 1.5 External Communications Ethernet, Wifi Internal Communications CAN bus Operating Temperature -10 +60 System Materials 1.5mm Stainless Steel 304 Warranty 24 Months Service Level Agreement 24 Months	Weight	21kg
Weight 7kg Power Supply (v) 24 Max Power Consumption (A) 1.5 External Communications Ethernet, Wifi Internal Communications CAN bus Operating Temperature -10 +60 System Materials 1.5mm Stainless Steel 304 Warranty 24 Months Service Level Agreement 24 Months	Dimensions	200 x 200 x 80
Power Supply (v) 24 Max Power Consumption (A) 1.5 External Communications Ethernet, Wifi Internal Communications CAN bus Operating Temperature -10 +60 System Materials 1.5mm Stainless Steel 304 Warranty 24 Months Service Level Agreement 24 Months	Colour	RAL 7016
Max Power Consumption (A) External Communications Internal Communications Operating Temperature -10 +60 System Materials 1.5mm Stainless Steel 304 Warranty 24 Months Service Level Agreement 24 Months	Weight	7kg
External Communications Internal Communications Operating Temperature -10 +60 System Materials 1.5mm Stainless Steel 304 Warranty 24 Months Service Level Agreement 24 Months	Power Supply (v)	24
Internal Communications Operating Temperature -10 +60 System Materials 1.5mm Stainless Steel 304 Warranty 24 Months Service Level Agreement 24 Months	Max Power Consumption (A)	1.5
Operating Temperature -10 +60 System Materials 1.5mm Stainless Steel 304 Warranty 24 Months Service Level Agreement 24 Months	External Communications	Ethernet, Wifi
System Materials 1.5mm Stainless Steel 304 Warranty 24 Months Service Level Agreement 24 Months	Internal Communications	CAN bus
Warranty 24 Months Service Level Agreement 24 Months	Operating Temperature	-10 +60
Service Level Agreement 24 Months	System Materials	1.5mm Stainless Steel 304
Service Levering Centeric 2	Warranty	24 Months
Standards CE and FCC	Service Level Agreement	24 Months
l l	Standards	CE and FCC

Features

- Locking Driver Key Slots
- Polycarbonate Viewing Window
- IP33 Rated
- Automated Reporting to e-Track Web Software
- Data Analytics With Visual Web Alarms
- Compliance Auditing
- Audible Alarm
- Simple Traffic Light System
- Integration With 3rd Party Safety Systems
- Dock Door Monitoring
- Anti-Tamper Alarms
- Night Lights For Ease of Use
- Minimal Maintenance
- Door Interlock
- Manual Override

e-Track.