

# e200 High Secure System Specifications



Key Positions	10 -200
External System Dimensions incl. plinth & controller (mm) (HxWxD)	1870 x 1030 x 180
Total System Weight (Kg)	230
System Materials	3mm Steel
Colour	RAL 7016, Anthracite Grey
Door Options	Reinforced solid steel
eFobs	RFID
LEDs	Multi-colour
Operating Temperature (°C)	-10 to max +60
Power Supply (v)	110 - 240
Max Power Consumption	4 Amps
Battery Backup	5.4 Ah Lead Acid
System Access	PIN, RFID, Biometric
Interface	5" screen with stainless steel keypad or 10" touchscreen display
Users per System	10,000 per application
Communications	Ethernet, WiFi, 4G
Mounting	Wall mounted
Manual Override	Mechanical
Warranty	24 months
Service Level Agreement	24 months
Standards	CE and FCC

## Features

- Tamper proof security rating
- Multi-point locking system
- Multi-factor access control
- Magnetic locks with sensory state detection
- Self closing mechanism
- Door ajar alarm
- Off set key positions for maximum hanging space
- Create a network of linked cabinets
- Dynamic key management across multiple sites
- Flexible API for 3rd party software integration
- Export analytics into PDF or CSV for further analysis or presentation
- Mobile compatible - pre book keys from any location
- Full control over all organisational keys at the click of a button
- Create user groups with common access levels
- Easy maintenance and service