

e10 Mini



Key Positions	1 - 10
External System Dimensions incl. plinth & controller (mm) (HxWxD)	410 x 430 x 125
Total System Weight (Kg)	19
System Materials	1.5mm mild steel
Colour	White
Door Options	Clear polycarbonate, dark transparent, solid steel
eFobs	RFiD
LEDs	Multi-colour
Operating Temperature (°C)	-10 to max +60
Power Supply (v)	110 - 240
Max Power Consumption	4 Amps
Battery Backup	5.4 Ah Lead Acid
System Access	PIN, RFiD, Biometric
Interface	5" screen with stainless steel keypad
Users per System	10,000 per application
Communications	Ethernet, WiFi, 4G
Mounting	Wall mounted
Manual Override	Mechanical and electronic
Warranty	24 months
Service Level Agreement	24 months
Standards	CE and FCC

Features

- Magnetic locks with sensory state detection
- Multi-colour LEDs with withdrawal and return indicators
- Off set key positions for maximum hanging space
- Create a network of linked cabinets
- Dynamic key management across multiple sites
- Flexible API for 3rd party software integration
- Export analytics into PDF or CSV for further analysis or presentation
- Mobile compatible - pre book keys from any location
- Full control over all organisational keys at the click of a button
- Create user groups with common access levels
- Easy maintenance and service